

87 links west of the true corner Bearing trees
 Beech 24 in. dia. S 77° W 11½ links Hick. 6 in. dia. N 40½° W 69¾ links
 thence on the same course 20 chains and established ¼ S on the North
 side of said section Stone Marked

Bearing tree W. Oak 20 in. Dia S 10½° W 22 links

Sassafras 5 " " N 29½° W 34¾

thence on the same 34.10 Chains to the NW ¼ corner of sd section
 thence S 6° E 28.41 Chains towards the SW ¼ corner and established
 ¼ S Dogwood 4 in. dia. S 47¾° E 38¾

Beech 5 " " N 81° E 38

thence on the same course 28.41 Chains and place a stake ^{no original}
 thence on the same course 40 chains to the SW Corner then returned
 to the aforesaid stake thence N 85½° E 17.95 Chains toward ¼ S on the
 East side of sd section and established ¼ S on the South side of NW ¼

Beech 24 in. dia N 83½° W 76 links

Elm 8 " " S 59° West 23¾ do

thence on the same course 17.95 and established ¼ Center S Bearing

W. Oak 24 S 10½° E 17½ links

W. Walnut 6 N 27° E 46 links

thence on the same course 20 chains and established ¼ S on the South
 side of the NE ¼ quarter Bearing tree Hick. 22 S 20° W 6 links

thence on the same course 20 chains to the ¼ S on the East side of sd section
 then returned to the last established Corner thence N 74° W 57.85 Chains

to ¼ S on the N side of the NE ¼ quarter then went to the ¼ S on the N side
 of sd section thence South 57° 30' E 58.32 Chains to ¼ Center S then return
 back on sd line 27.16 Chains and established ¼ S Bearing trees

W. Oak 8 S 81° E 20 links W. Oak 24 N 59° E 25 links

thence S 84° 50' W 34.78 Chains to ¼ S on the West side of the NW ¼ quarter
 then returned back 17.39 Chains and established ¼ Center S to NW ¼ quarter

Elm 3 in. dia. S 47° W 6 links Cherry 5 in. dia. N 36° E 7¾ links

thence S 6° 45' E to ¼ S on the South side of the NW ¼ quarter

Then went to the ¼ S between the ¼ Center S and ¼ S on the North thence
 N 85° E 40 Chains to ¼ S on the East side said ^{section} of the NE ¼ quarter then
 returned back on sd line 20 chains and established ¼ Center S to
 NE ¼ quarter where sd line crosses the line running from ¼ S on the
 South side of the NE ¼ quarter to ¼ S on the N side of sd quarter

Stone Marked ¼ S Sassafras 5 in. dia. S 18½° W 39

do 4 " " N 88½° E 42

Nathan Baker { Chain Bearers

John O. Fellows { first day

Eli Fancett

Galigan Schraug { 2 day

9 Corners + 9 lines beside the
 establishing of NE Corner.

J. C. Brown, Surveyor of S. C.

April 20 Surveyed for Floyd Collins + Geo. Burch in Section 3
 in Town No. 7 North Range No. 3 Beginning at the ¼ S on the West side
 of sd section thence N 84½° E 79.37 Chains to ¼ S on the East side of sd sect.
 then returned back on sd line 38.68½ Chains and established ¼ Center
 S for the South ½ of sd section by consent of all parties interested
 Sand Rock marked with a X Bearing tree

Black Walnut 1 in. dia. N 6° E 6 links

Beech 6 " " S 7¾° W 23¼ links

thence S 6½° E 39.85 Chains to ¼ S on the South then went back on
 sd line 19.92½ Chains ½ distance to Center ¼ and established ¼ S
 Sand Rock marked X Bearing tree Gum 12 in. dia. S 50° W 15½ links
 do 3 " " N 29° E 11½ do

Ambrose Stone, Geo. Burch, Junr.

+ Reuben Beasely, Chain Bearers.

J. C. Brown, Surveyor.

May 2, 1843 Surveyed for Emanuel Hatfield and Elias Copeland
 in Section 27 in Town No. 6 North + Range No. 3 West Beginning at
 the NE Corner thence S 7½° E. 39.83 Chains to ¼ on the East thence S
 83° 50' West 80.22 Chains to ¼ S on the West side of sd section then went to
 the ¼ S on the South thence N 7¼° W 79.08 Chains to ¼ on the North then
 returned on sd line to the point where said last two lines cross
 each other at right angles and established ¼ Center S Sand
 Rock Marked with a X Bearing trees Hick. 18 in. dia. S 42° W 26 links

do 14 " " S 77° E 44 do

Making from Center ¼ to ¼ S on the north 39.58 Chains